

Blower Heater Combinations

Blower	Airheater	max No.	KW per heater	Volt	max Temperature °C	minimum airflow l/min
Robust	Labo 34	2	0.8	230	600	100
Robust	Typ 700	2	0.77	230	600	100
Robust	Typ 3000	2	3.3	230	650	300
Robust	Typ 3300	2	3.6	230	650	350
Robust	Typ 3300	2	4.4	400	650	350
Silence	Typ 3300	2	3.6	230	650	350
Silence	Typ 3300	2	4.4	400	650	350
ASO	Typ 3300	8	3.6	230	650	350
ASO	Typ 3300	6	4.4	400	650	350
Air Pack	Typ 3300	8	3.6	230	650	350
Air Pack	Typ 3300	8	4.4	400	650	350
Silence	Typ 5000	2	5	400	700	500
Silence	Typ 5000	2	8	400	700	800
ASO	Typ 5000	4	5	400	700	500
ASO	Typ 5000	4	8	400	700	800
Air Pack	Typ 5000	4	5	400	700	500
Air Pack	Typ 5000	4	8	400	700	800
Silence	Typ 10000 S	2	11	400	650	1000
Silence	Typ 10000 S	2	17	400	650	1750
ASO	Typ 10000 S	4	11	400	650	1000
ASO	Typ 10000 S	4	17	400	650	1750
Air Pack	Typ 10000 S	2	11	400	650	1000
Air Pack	Typ 10000 S	2	17	400	650	1750
ASO	Typ 40000	1	32	488	700	2800
Air Pack	Typ 40000	1	32	400	700	2800
ASO	Typ 5000 HT	1	11	400	900	1000
Robust	Typ 5000 HT	1	11	400	900	1000



Note that airheaters can be used with clean and dry compressed air but this must be pressure reduced and minimum air flow must be guaranteed. We recommend the use of air blowers for larger units.